



## Features

- Long-life elastomer diaphragm
- High-quality snap-action switch
- Factory preset
- Available in a wide range of configurations
- Economical
- Pneumatic and hydraulic applications
- NEMA 4, 13

## Operating Specifications

<b>Set Point Range</b>	2 — 120 PSI	(.14 — 8.3 Bar)
<b>Set Point Tolerance</b>	±1 PSI or 5%	(.07 Bar)
<b>Maximum Operating Pressure</b>	600 PSI	(41 Bar)
<b>Proof Pressure</b>	1800 PSI	(124 Bar)
<b>Differential</b>	8 — 16%	
<b>Current Rating</b>	5 A @ 250 VAC	5 A @ 30 VDC (Resistive)
<b>Media Connection</b>	See Order Chart Below for Options	
<b>Circuit Form</b>	SPST-NO, SPST-NC or SPDT	
<b>Electrical Connection</b>	See Order Chart Below for Options	
<b>Diaphragm Material</b>	Buna N	
<b>Cycle Life</b>	1 Million	

## How to Order (Example: Part Number: **MM - 6A - 80R / WL** \*)

<b>MM</b> -	<b>6</b>	<b>A</b>	-	<b>8</b>	<b>0</b>	<b>R</b>	/	<b>WL</b>	*
<b>Media Connection</b>		<b>Circuit Form</b>		<b>Fixed Set Point</b>		<b>Set Point Direction</b>		<b>Electrical Options</b>	
<b>1</b> 1/4" NPT Male		<b>A</b> SPST-NO		<b>2 — 120</b> PSI		<b>R</b> Rising		<b>WL</b> Wire Leads 18"	
<b>2</b> 1/8" NPT Male		<b>B</b> SPST-NC				<b>F</b> Falling		<b>QC</b> 1/4" Spade Connection	
<b>6</b> 7/16" SAE O-Ring (-4)		<b>C</b> SPDT						<b>WP</b> Weather Pack	
<b>14</b> 1/2" NPT Male 1/8" NPT Female								<b>HR</b> DIN43650A Connector	
<b>17</b> 1/4" BSPP Male (G1/4)								<b>MP</b> Metri-Pack	
<b>28</b> 1/8" BSPP Male (G1/8)								<b>AT</b> 10 A @ 125/250 VAC 5 A @ 30 VDC	
								<b>GG</b> Internal Ground	
								<b>AU</b> Gold Plate/Alloy for low currents	

To order call 800-333-7976 or email [info@partdeal.com](mailto:info@partdeal.com)