



Features

- Utilizes bellows mechanism to sense temperature
- High-quality snap-action switch
- Factory preset
- Shock and vibration resistant
- Available in a wide range of configurations
- NEMA 4, 13

Operating Specifications

Set Point Range	40° — 300°F	(4° — 149°C)
Set Point Tolerance	±5°F	(2.8°C)
Maximum Operating Temperature	100°F above set point (325°F max)	
Differential	8 — 16°F	
Current Rating	10 A @ 125/250 VAC	5 A @ 30 VDC
Media Connection	See Order Chart Below for Options	
Circuit Form	SPST-NO, SPST-NC or SPDT	
Electrical Connection	See Order Chart Below for Options	
Maximum External Pressure	500 PSI	

How to Order (Example: Part Number: HT - 2A - 100R / WL)

HT - **2** **A** - **1** **0** **0** **R** / **WL** *

<p>Media Connection</p> <p>1 1/2" NPT Male</p> <p>2 3/8" NPT Male</p> <p>6 M16 x 1.5</p> <p>7 1/2" BSPP Male (G1/2)</p>	<p>Circuit Form</p> <p>A SPST-NO</p> <p>B SPST-NC</p> <p>C SPDT</p>	<p>Fixed Set Point</p> <p>40°F — 300°F</p>	<p>Set Point Direction</p> <p>R Rising</p> <p>F Falling</p>	<p>Electrical Options</p> <p>WL Wire Leads 18"</p> <p>QC 1/4" Spade Connection</p> <p>WP Weather Pack</p> <p>HR DIN43650A Connector</p> <p>MP Metri-Pack</p> <p>AH 25 A @ 277 VAC 5 A @ 30 VDC</p> <p>GG Internal Ground</p> <p>AU Gold Plate/Alloy for low currents</p>
--	---	--	--	---

To order call 800-333-7976 or email info@partdeal.com



* Defaults to Screw Terminals